


# **BX28**



BX28 is active dual 18" subwoofer.

The power amplifier module adopts 2x2200W class D, can provide scene presets, capable of providing up to 141dB SPLmax (1 m under half space in a single cabinet).

Premium grade birch plywood cabinet, CNC manufacturing process, black polyurea spray coating, durable and long-lasting It can be stacked vertically and horizontally.

This product is designed for small and medium-sized tours, as well as reinforcement for medium throwing distances.

#### Electroacoustic:

Input sensitivity:32dB Short term SPLmax: 141dB([100]preset) (Peak level at 1 m under half space) Frequency Response:32~200Hz Electric power:96~265VAC 50~60 Hz Transducers:

2x18"Carbon fiber cone ferrite driver (V.C:4"8)

Acoustical load:bass-reflex

Directivity:

standard or cardioid(processed)

Power amplifier:

Power:2x2200WRMS@8 CLASS D Cooling:Forced air cooling Processor:24Bit /96k DSP

### Connection and Control:

2xPowerCon TRUE1(Power)

2xXLR parallel(Audio)

DSP control:TCP/IP(Windows)

(Select the preset touch surface on the touch panel)

Cabinet: premium grade birch plywood made by CNC

handling:


4 handles/2 M10 threaded inserts/4 ground runners

Front:steel grill with coating acoustically neutral 3D fabric

Finish: black polyurea spot spray

Product DIM(mm): W1065xH560xD780


Net weight: 97kg/214lb



## **Amplifier panel**

## **Connectors:**

The BX28 equipped with two PowerCon TRUE1(Power)/XLR(Audio)/RJ45(DSP control) connectors wired in through. equipped with a touch panel to select scene presets.



Touch control preset mode selection

## Display panel:





www.saeaudio.com

